



Description	
Joystick Type SK 315-0122	
Number of axes	2-axes, x-axis, y-axis both axes are redundant
Operation by	Rubber bellow
Cross guidance	rigid
Retaining spring	normal, Z-Nr. 60-112
Connector:	Minitek Shrouded Header 8-poles
Mating connector:	Minitek IDC Receptacle, 8-poles
Electrical characteristics	
Operating voltage	5 V DC
Sensor	Hall effect technology
Pin	
01	Supply voltage
02	x1 (-x=0.5V, middle=2.5V, +x=4.5V)
03	Ground
04	y1 (-y=0.5V, middle=2.5V, +y=4.5V)
05	y2 (-y=4.5V, middle=2.5V, +y=0.5V)
06	do not use
07	x2 (-x=4.5V, middle=2.5V, +x=0.5V)
08	do not use

		Oberfläche	Maßstab 1:1	Position -	Menge -
		Joystick			
		315-0122			
		Blatt -			
		BI			
Zust.	Änderungen	Datum	Name		
		Bearb. 14.12.14	DR		
		Gepr.			
		Norm			
		Genge & Thoma AG joysticks & sensors		GT	
				S:\Entwicklung\01_CAD-Daten\02_DWG\DWG_SK315\Typenzeichnungen\315-0122.dwg	