



Description	
Joystick type SK 315-009	
Number of axes	3-axes, x-axis, y-axis, z-axis all three axes are redundant
Operation by	Handle with z-axis ($\pm 30^\circ$)
Cross guidance	soft
Retaining spring	normal, Z-Nr. 60-112
Connector:	Minitek Shrouded Header 8-poles
Mating connector:	Minitek IDC Receptacle, 8-poles
Electrical characteristics	
Operating voltage	5 V DC
Sensor	Hall effect technology
Pin	
01	Supply voltage
02	x1 (-x=0.5V, middle=2.5V, +x=4.5V)
03	Ground
04	y1 (-y=0.5V, middle=2.5V, +y=4.5V)
05	y2 (-y=0.5V, middle=2.5V, +y=4.5V)
06	z2 (-z=0.5V, middle=2.5V, +z=4.5V)
07	x2 (-x=0.5V, middle=2.5V, +x=4.5V)
08	z1 (-z=0.5V, middle=2.5V, +z=4.5V)

				Oberfläche	Maßstab 1:1	Position	Menge
				Datum	Name	Joystick	
				Bearb. 09.03.11	Kiener M.		
				Gepr.			
				Norm			
c	AEN-15-020/AEN-15-033	07.01.16	MK	GENGE & THOMA AG OH-2543 Lengnau/Blai			Blatt
b	AEN-13-044	29.10.13	MK				
a	Neue Vers., Plastikflansch	12.12.12	MK				
Zust.	Anderungen	Datum	Name	Dateiname	E:\DW\SK 315\SK315-009c.dwg	315-009c	