


KEL-FG-E

Flange enclosures
for cable entry



Slit grommets

1

Description

Type

Order No.

Grommets
small | large

PU

Product description

The cable entry frames KEL-FG-E are suited for installation, sealing and strain relief of cables with connectors and conduits at an angle of 90° to the cabinet, enclosure or machine wall. For routing cables and conduits up to 17 mm in diameter.

The KEL-FG-E version is particularly suited for flat connectors. The small frame is ideal for applications with limited space. A flat rubber gasket is included in the shipment.

Advantages & benefits


- Installation at an angle of 90° to the wall
- Mechanical protection of cable directly at the place of entry
- Protection against water spray and drips
- Warranty on pre-terminated cables remains
- Space saving shape
- Optimal for D-Sub connectors
- Strain relief according to EN 62444
- High stability, vibration resistant

Specifications

Material	Polyamide (PA)
Flame class	UL94-V0, self-extinguishing
IP rating	IP54, with gasket and correct selection of the cable grommets
Temperature	- 40°C to + 140°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	E3: 65 × 24 mm E5: 112 × 24 mm

Accessories

Cable grommets	44 - 48
KEL-EMC Cable collectors	122 - 124



KEL-FG-E3

42334

3|-


5

KEL-FG-E3
with V2A
screws

42334.200

3|-

5



KEL-FG-E5

42336

5|-

5

KEL-FG-E5
with V2A
screws

42336.200

5|-

5

