

## **Product Description**

- GQ12-C series is Latching Type Product which is developed on the basis of GQ12-A.
- And all the electrical properties of GQ12-C are the same as GQ12-A series except the following items Switch Rating: 1A/36V LED Voltage: Red&Yellow&Orange AC/DC 1.8V

  - Green&Blue&White 2.8V
  - all the Voltage need to connect an outer risistor.

## Part-number Description

## **Related parameters**

Terminal Type	Pin Terminal(2.8×0.5mm) x(double-break and slow	Material of Actuator	Stainless Steel
Switching: Panel	-motion contact) 1~10mm	The Crust Material	Stainless Steel
Thickness		Material of Base	PA66
Torque	About 0.6Nm	Operation	About 3.5N
Mechanical	More than 200,000 cycles	Pressure	
Life	More man 200,000 cycles	Operation Travel	About 2.5mm
Electrical Life	More than 50,000 cycles		

GQ12-C	* -	- 🗆	Z	J /	0
Code of series	The Front Shape	Contact Structure	Operation Type	Terminal Type	The Crust Material
	H Flat head +High button	10 1NO	Z Latching If you need Momentary Type, pls choose GQ12-A series.	J Pin Terminal	S Stainless Steel Other Material can be made to order.

Note: PIs read the catalogue carefully, and choose the right part-number according to the sign.

## GQ12-CH-10Z/J/S Stainless Steel

- Oiameter: Φ12mm
- Switch Rating:1A/36V
- Ontact Configuration:1NO
- Operation Type:Latching(Z)
- The Crust Material: Stainless steel
- IP Degree:IP40
- Iterminal Type:Pin Terminal(2.8×0.5mm)

